

ARIL SUSPENDED

The Playful.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - INDIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE

Minimalist and classic in design, the Aril is a clean cut linear pendant that can take your interior design to the next level. With the driver included in its slim body, there is no need for remote drivers, making the Aril a perfect linear lighting for spaces with low ceiling void.

The clean aesthetics of the 28mm wide body will enhance any modern space. The highly high level of finish will allow the luminaire to be viewed from any angle, making it a great choice for atriums, viewing galleries and large stair cases.

With 6 different lengths to choose from, the Aril allows for a comprehensive range of applications. Ideal as architectural lighting for breakout spaces, reception areas and public areas.

PRODUCT CODE

ARIL SUSPENDED			
L (mm)	LED	Medium Output - Direct	Product Code
847	LED	1x18W / 1760 lm	44-E*1-F2-847-***-***
1127	LED	1x23W / 2350 lm	44-E*1-F2-1127-***-***
1408	LED	1x30W / 2940 lm	44-E*1-F2-1408-***-***
1688	LED	1x35W / 3530 lm	44-E*1-F2-1688-***-***
1969	LED	1x41W / 4120 lm	44-E*1-F2-1969-***-***
2249	LED	1x47W / 4710 lm	44-E*1-F2-2249-***-***
Medium Output - Direct/Indirect			
847	LED	1x24W / 2510 lm	44-E*3-F2-847-***-***
1127	LED	1x35W / 3850 lm	44-E*3-F2-1127-***-***
1408	LED	1x47W / 5190 lm	44-E*3-F2-1408-***-***
1688	LED	1x58W / 6530 lm	44-E*3-F2-1688-***-***
1969	LED	1x70W / 7870 lm	44-E*3-F2-1969-***-***
2249	LED	1x82W / 9210 lm	44-E*3-F2-2249-***-***

*Luminous flux taken at 4000K Opal diffuser

OPTICS			
MICROPRISMATIC	OPAL	PRISMATIC	44-EF1-F-***-***-***
		OPAL	44-EH1-F-***-***-***
		Low UGR Louvre	44-EQ1-F-***-***-***

OUTPUT			
Low Output	Medium Output	Low Output	44-E*1-F1-***-***-***
		Medium Output	44-E*1-F2-***-***-***
<small>*Low output approximately 35% decrease in power & 35% decrease in lumens against Medium Output</small>			
CRI			
80		80	44-E*1-F-***-g***-***
COLOUR TEMPERATURE			
3000K	4000K	3000 K	44-E*1-F-***-30-***
		4000 K	44-E*1-F-***-40-***
CONTROL			
NONDIM	DALI DIM	DALI 2 DIM	CASAMBI
		NON DIM	44-E*1-F-***-***-Jc-***
		DALI DIM	44-E*1-F-***-***-J-***
		DALI 2 DIM	44-E*1-F-***-***-JA-***
		CASAMBI DIM	44-E*1-F-***-***-B-***
<small>*EasyAir IoT on request</small>			
EMERGENCY			
NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY REMOTE	3 HOUR REPORTING EMERGENCY REMOTE	3 HOUR SELF-TEST EMERGENCY REMOTE
		No Emergency	44-E*1-F-***-***-0-***
		3 Hour Non Reporting EM	44-E*1-F-***-***-7-***
		3 Hour Reporting EM	44-E*1-F-***-***-g-***
		3 Hour Self-Test EM	44-E*1-F-***-***-g-***
<small>*Only available as remote emergency</small>			
FINISH			
BLACK	WHITE	SILVER	CUSTOMRAL
		BLACK	44-E*1-F-***-***-D
		WHITE	44-E*1-F-***-***-C
		GREY	44-E*1-F-***-***-B
		CUSTOM RAL	44-E*1-F-***-***-RAL####

