



CLYDE SUSPENDED DIRECT-INDIRECT

Ready When You Are.

PRODUCT DESCRIPTION

| | |
|---------------------------|-------------------|
| MOUNTING | SUSPENDED |
| LIGHT SOURCE | LED |
| LIGHT DISTRIBUTION | DIRECT - INDIRECT |
| MATERIALS | ALUMINIUM |
| LUMINAIRE TYPE | COMPLETE |

The CLYDE Suspended direct-indirect is the ultimate comfort driven linear profile. Designed and manufactured in the UK, the CLYDE is the first Made in Britain certified luminaire in our product range. Thanks to its high build quality, excellent performance, and high visual comfort it is a perfect linear lighting for stimulating working environments and projects looking to use sustainable product options.


Used as an individual luminaire or a continuous linear lighting system, the CLYDE adds a contemporary feel to any workplace or architectural spaces, giving the interiors an extra lift. The muscular design of the CLYDE stands out and lends itself perfectly to made to measure linear lighting solutions with a bit of a presence in space.

PRODUCT CODE

CLYDE SUSPENDED DI

| L (mm) | Low Output | Medium Output | High Output |
|--------|----------------------------|-----------------------------|----------------------------|
| 568mm | LED 13.8W / 1572 lm | LED 17.9W / 1940 lm | LED 21.6W / 2289 lm |
| 848mm | LED 23.0W / 2674 lm | LED 29.8W / 3300 lm | LED 36.0W / 3895 lm |
| 1128mm | LED 32.2W / 3777 lm | LED 41.7W / 4661 lm | LED 50.4W / 5501 lm |
| 1408mm | LED 41.4W / 4879 lm | LED 53.6W / 6022 lm | LED 64.8W / 7107 lm |
| 1688mm | LED 50.6W / 5982 lm | LED 65.5W / 7382 lm | LED 79.2W / 8713 lm |
| 2248mm | LED 69.0W / 8187 lm | LED 89.3W / 10104 lm | LED 108W / 11925 lm |

*Luminous Flux taken with 4000K 1 Opal Diffuser



OPTICS

| | | | | |
|----------------|------|------|-----------|----------------------------|
| MICROPRISMATIC | OPAL | QUAD | PRIS-OPAL | 83-EF3-F1-***-***-* |
| | | | QUAD | 83-EH3-F1-***-***-* |
| | | | | 83-EG3-F1-***-***-* |

**Uplight diffuser opal as standard*

CRI

| | | | |
|--------|--------|--------|-------------------------------|
| CRI 80 | CRI 90 | CRI 80 | 83-E*3-F*-***-g**-*-* |
| | | CRI 90 | 83-E*3-F*-***-g***-*-* |

COLOUR TEMPERATURE

| | | | | |
|-------|-------|---------------|-------|-----------------------------|
| 3000K | 4000K | TW 2700-6500K | 3000K | 83-E*3-F1-***-30-*-* |
| | | | 4000K | 83-E*3-F1-***-40-*-* |
| | | | TW | 83-E*3-F1-***-TW-*-* |

CONTROL

| | | | |
|---------|----------|----------|--------------------------|
| NON DIM | DALI DIM | NON DIM | 83-E*3-F*-***-K-* |
| | | DALI DIM | 83-E*3-F*-***-J-* |

**DALI-DIM as standard*

EMERGENCY

| | | | |
|--------------|------------------|------|--------------------------|
| NO EMERGENCY | 3 HOUR EMERGENCY | 0 HR | 83-E*3-F*-***-0-* |
| | | 3 HR | 83-E*3-F*-***-3-* |

**Emergency available from 1128mm*

FINISH

| | | | | |
|-------|-------|--------|--------|------------------------|
| WHITE | BLACK | SILVER | WHITE | 83-E*3-F*-***-C |
| | | | BLACK | 83-E*3-F*-***-D |
| | | | SILVER | 83-E*3-F*-***-B |

LAST UPDATED JANUARY 2024

