



EBRO SUSPENDED

The Power Of Geometry.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT, DIRECT / INDIRECT
MATERIALS	ALUMINIUM

The ERBO Suspended is the perfect lighting to embed a modern feel in any environment the moment you step in. With its simple and minimalist structure.

Ideal for a vast range of environments from offices to lobby areas or even retail lighting, this luminaire is a highly versatile product which will be appreciated by all wherever it's situated.

*Product is also available as surface, wall and recessed mounting styles.
More details are coming soon. Please contact the office for further information.

PRODUCT CODE

EBRO SUSPENDED DIRECT		
l (mm)	High Efficiency	
630x630mm	LED 50W / 5625 lm	68-F*1-F2-630x630-***-***-*
910x910mm	LED 75W / 8438 lm	68-F*1-F2-910x910-***-***-*
1190x1190mm	LED 100W / 11250 lm	68-F*1-F2-1190x1190-***-***-*
1470x1470mm	LED 125W / 14063 lm	68-F*1-F2-1470x1470-***-***-*
1750x1750mm	LED 150W / 16875 lm	68-F*1-F2-1750x1750-***-***-*
910x1540mm	LED 103W / 11602 lm	68-F*1-F2-910x1540-***-***-*
910x1850mm	LED 116W / 13008 lm	68-F*1-F2-910x1850-***-***-*
910x2380mm	LED 140W / 15820 lm	68-F*1-F2-910x2380-***-***-*
1190x1540mm	LED 116W / 13008 lm	68-F*1-F2-1190x1540-***-***-*
1190x1820mm	LED 128W / 14414 lm	68-F*1-F2-1190x1820-***-***-*
1190x2380mm	LED 153W / 17227 lm	68-F*1-F2-1190x2380-***-***-*

* Luminous Flux taken with 4000K / Opal Diffuser

EBRO SUSPENDED DIRECT / INDIRECT		
l (mm)	High Efficiency	
630x630mm	LED 88W / 10628 lm	68-F*3-F2-630x630-***-***-*
910x910mm	LED 137W / 16701 lm	68-F*3-F2-910x910-***-***-*
1190x1190mm	LED 187W / 22774 lm	68-F*3-F2-1190x1190-***-***-*
1470x1470mm	LED 237W / 28847 lm	68-F*3-F2-1470x1470-***-***-*
1750x1750mm	LED 287W / 34920 lm	68-F*3-F2-1750x1750-***-***-*
910x1540mm	LED 165W / 20117 lm	68-F*3-F2-910x1540-***-***-*
910x1850mm	LED 178W / 21635 lm	68-F*3-F2-910x1850-***-***-*
910x2380mm	LED 203W / 24672 lm	68-F*3-F2-910x2380-***-***-*
1190x1540mm	LED 203W / 24672 lm	68-F*3-F2-1190x1540-***-***-*
1190x1820mm	LED 215W / 26190 lm	68-F*3-F2-1190x1820-***-***-*
1190x2380mm	LED 240W / 29226 lm	68-F*3-F2-1190x2380-***-***-*

* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS		
MICROPRISMATIC	OPAL	PRISMATIC OPAL
		68-F*3-F*1-***x***-***-***-*
		68-F*1-F*1-***x***-***-***-*

* Nero optic available on request

CRI		
80	90	80 68-F**F*-***x***-g**-*-* 90 68-F**F*-***x***-g**-*-*

COLOUR TEMPERATURE		
2700K	3000K	2700K 68-F**F*-***x***-27-*-* 3000K 68-F**F*-***x***-30-*-* 4000K 68-F**F*-***x***-40-*-* 5000K 68-F**F*-***x***-50-*-* TW 68-F**F*-***x***-TW-*-*
4000K	5000K	
TW	2700-5000K	

CONTROL		
NON DIM	DALI DIM	NON DIM 68-F**F*-***x***-K-*-* DALI DIM 68-F**F*-***x***-J-*-* EASY AIR PIR 68-F**F*-***x***-Q-*-* B. DALI DIM 68-F**F*-***x***-M-*-*
EasyAir PIR/ Daylight DIM	DALI DIM BLUETOOTH	

EMERGENCY		
NO EMERGENCY	3 HOUR EMERGENCY	0 HR 68-F**F*-***x***-0-*-* 3 HR 68-F**F*-***x***-3-*-*

FINISH		
WHITE	BLACK	WHITE 68-F**F*-***x***-C BLACK 68-F**F*-***x***-D SILVER 68-F**F*-***x***-B
SILVER		

