

LECK RECESSED TRIM

The Micro Linear.

PRODUCT DESCRIPTION

MOUNTING	RECESSED TRIM
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE


The Leck Recessed Trim is a seemingly simple architectural profile luminaire, forming a thin line of continuous light. Increasingly popular with architects and designers, the Leck can be used as a system throughout the entire project- as a recessed line, surface mounted or as a suspended pendant.

Blending seamlessly into the background, the continuous lighting Leck Recessed provides, is versatile enough to follow structural design and room geometries with its wide selection of modules. Available in four different finishes, it is suitable for offices, retail, galleries, lobby areas and healthcare.

PRODUCT CODE

LECK RECESSED TRIM

L (mm)	High Efficiency	
706	LED	1x29W / 3417 lm
776	LED	1x32W / 3796 lm
846	LED	1x35W / 4176 lm
916	LED	1x38W / 4555 lm
986	LED	1x41W / 4935 lm
1056	LED	1x44W / 5314 lm
1126	LED	1x47W / 5694 lm
1196	LED	1x50W / 6073 lm
1266	LED	1x53W / 6453 lm
1336	LED	1x56W / 6832 lm
1406	LED	1x60W / 7212 lm
1476	LED	1x63W / 7592 lm
1546	LED	1x66W / 7971 lm
1616	LED	1x69W / 8351 lm
1686	LED	1x72W / 8730 lm
1756	LED	1x75W / 9110 lm
1826	LED	1x78W / 9489 lm
1896	LED	1x81W / 9869 lm
1966	LED	1x85W / 4176 lm
2036	LED	1x88W / 10628 lm
2106	LED	1x91W / 11008 lm
2176	LED	1x94W / 11387 lm
2246	LED	1x97W / 11767 lm
2316	LED	1x100W / 12146 lm
2386	LED	1x103W / 12526 lm
2456	LED	1x106W / 12905 lm
2526	LED	1x109W / 13285 lm
2596	LED	1x113W / 13665 lm
2666	LED	1x116W / 14044 lm
2736	LED	1x119W / 14424 lm
2806	LED	1x122W / 14803 lm



*Luminous flux taken at 4000K Opal diffuser

36-A*1-F2-706-***-***-***
36-A*1-F2-776-***-***-***
36-A*1-F2-846-***-***-***
36-A*1-F2-916-***-***-***
36-A*1-F2-986-***-***-***
36-A*1-F2-1056-***-***-***
36-A*1-F2-1126-***-***-***
36-A*1-F2-1196-***-***-***
36-A*1-F2-1266-***-***-***
36-A*1-F2-1336-***-***-***
36-A*1-F2-1406-***-***-***
36-A*1-F2-1476-***-***-***
36-A*1-F2-1546-***-***-***
36-A*1-F2-1616-***-***-***
36-A*1-F2-1686-***-***-***
36-A*1-F2-1756-***-***-***
36-A*1-F2-1826-***-***-***
36-A*1-F2-1896-***-***-***
36-A*1-F2-1966-***-***-***
36-A*1-F2-2036-***-***-***
36-A*1-F2-2106-***-***-***
36-A*1-F2-2176-***-***-***
36-A*1-F2-2246-***-***-***
36-A*1-F2-2316-***-***-***
36-A*1-F2-2386-***-***-***
36-A*1-F2-2456-***-***-***
36-A*1-F2-2526-***-***-***
36-A*1-F2-2596-***-***-***
36-A*1-F2-2666-***-***-***
36-A*1-F2-2736-***-***-***
36-A*1-F2-2806-***-***-***

OPTICS

80	90	80	36-A*1-F*-***-g***-***-*
		90	36-A*1-F*-***-g***-***-*

COLOUR TEMPERATURE

2700K	3000K	2700 K	36-A*1-F*-***-27-***-***
		3000 K	36-A*1-F*-***-30-***-***
		4000 K	36-A*1-F*-***-40-***-***
		5000 K	36-A*1-F*-***-50-***-***
		TW	36-A*1-F*-***-TW-***-***
4000K	5000K		
TW	2700K-5000K		

CONTROL

NON DIM	DALI DIM	NON DIM	36-A*1-F*-***-***-K-***-*
		DALI DIM	36-A*1-F*-***-***-J-***-*

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	36-A*1-F*-***-***-0-***-*
		3 HR	36-A*1-F*-***-***-3-***-*

*Only available in sizes above 1265mm.

FINISH

BLACK	WHITE	BLACK	36-A*1-F*-***-***-D-***-*
		WHITE	36-A*1-F*-***-***-C-***-*
		GREY	36-A*1-F*-***-***-B-***-*
GREY			

INTERNAL REFLECTOR (MODULAR OPTIC ONLY)

BLACK	WHITE	BLACK	36-F*1-F*-***-***-***-D-***-*
		WHITE	36-F*1-F*-***-***-***-C-***-*

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC	36-AF1-F*-***-***-***-***
		OPAL	36-AH1-F*-***-***-***-***
		ASYMMETRIC	36-AB1-F*-***-***-***-***
		BLACK OPAL	36-AN1-F*-***-***-***-***
		MOD NARROW	36-AZ31-F*-***-***-***-***
		MOD WIDE	36-AZ61-F*-***-***-***-***
ASYMMETRIC	BLACK OPAL		
MODULAR NARROW BEAM	MODULAR WIDE BEAM		