



LECK SURFACE

The Micro Linear.

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE

The Leck Surface is a seemingly simple architectural profile luminaire, forming a thin line of continuous light. Increasingly popular with architects and designers, the Leck can be used as a system throughout the entire project- as a recessed line, surface mounted or as a suspended pendant.

Blending seamlessly into the background, the continuous lighting Leck Surface provides, is versatile enough to follow structural design and room geometries with its wide selection of modules. Available in four different finishes, it is suitable for offices, retail, galleries, lobby areas and healthcare.

PRODUCT CODE

LECK SURFACE

L (mm)	High Efficiency	
561mm	LED 7.7W / 720 lm	36-F*1-F72-8**-*0-*
842mm	LED 11.6W / 1090 lm	36-F*1-F10-8**-*0-*
1122mm	LED 15.5W / 1450 lm	36-F*1-F14-8**-*0-*
1403mm	LED 19.3W / 1820 lm	36-F*1-F18-8**-*0-*
1683mm	LED 23.2W / 2180 lm	36-F*1-F21-8**-*0-*
2244mm	LED 30.9W / 2910 lm	36-F*1-F29-8**-*0-*
High Output		
561mm	LED 11W / 990 lm	36-F*1-F99-8**-*0-*
842mm	LED 16.5W / 1490 lm	36-F*1-F15-8**-*0-*
1122mm	LED 22W / 1990 lm	36-F*1-F19-8**-*0-*
1403mm	LED 27.6W / 2490 lm	36-F*1-F24-8**-*0-*
1683mm	LED 33.1W / 2990 lm	36-F*1-F30-8**-*0-*
2244mm	LED 44.1W / 3980 lm	36-F*1-F39-8**-*0-*

*Luminous Flux taken with 4000K / Opal Diffuser



OPTICS

OPAL		OPAL 36-FH1-F**-8**-*0-*
LOWERED OPAL		LOW OPAL 36-FHL1-F**-8**-*0-*

*Opal diffuser as standard

COLOUR TEMPERATURE

3000K	4000K	3000K 36-F*1-F**-830-*0-*
		4000K 36-F*1-F**-840-*0-*

CONTROL

NON DIM	DALI DIM	NON DIM 36-F*1-F**-8**-*K0-*
		DALI DIM 36-F*1-F**-8**-*J0-*

FINISH

WHITE	BLACK	SILVER	WHITE 36-F*1-F**-8**-*0-C
			BLACK 36-F*1-F**-8**-*0-D
			SILVER 36-F*1-F**-8**-*0-B

