



LECK SUSPENDED

The Micro Linear.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE

The Leck Suspended Direct is a seemingly simple architectural profile luminaire, forming a thin line of continuous light. Increasingly popular with architects and designers, the Leck can be used as a system throughout the entire project- as a recessed line, surface mounted or as a suspended pendant.

Blending seamlessly into the background, the suspended continuous lighting Leck Suspended provides is versatile enough to follow structural design and room geometries with its wide selection of modules. Available in four different finishes, it is suitable for offices, retail, galleries, lobby areas and healthcare.

PRODUCT CODE

LECK SUSPENDED DIRECT

L (mm)	LED	Medium Output	Product Code
706	LED	1x16W / 1712 lm	36-E*1-F2-706-***-***
776	LED	1x18W / 1883 lm	36-E*1-F2-776-***-***
846	LED	1x19W / 2054 lm	36-E*1-F2-846-***-***
916	LED	1x21W / 2225 lm	36-E*1-F2-916-***-***
986	LED	1x22W / 2396 lm	36-E*3-F2-986-***-***
1056	LED	1x24W / 2567 lm	36-E*1-F2-1056-***-***
1126	LED	1x25W / 2738 lm	36-E*1-F2-1126-***-***
1196	LED	1x27W / 2909 lm	36-E*1-F2-1196-***-***
1266	LED	1x28W / 3080 lm	36-E*1-F2-1266-***-***
1336	LED	1x30W / 3252 lm	36-E*1-F2-1336-***-***
1406	LED	1x32W / 3423 lm	36-E*1-F2-1406-***-***
1476	LED	1x33W / 3594 lm	36-E*1-F2-1476-***-***
1546	LED	1x35W / 3765 lm	36-E*1-F2-1546-***-***
1616	LED	1x36W / 3936 lm	36-E*1-F2-1616-***-***
1686	LED	1x38W / 4107 lm	36-E*1-F2-1686-***-***
1756	LED	1x39W / 4278 lm	36-E*1-F2-1756-***-***
1826	LED	1x41W / 4449 lm	36-E*1-F2-1826-***-***
1896	LED	1x42W / 4620 lm	36-E*1-F2-1896-***-***
1966	LED	1x44W / 4792 lm	36-E*1-F2-1966-***-***
2036	LED	1x46W / 4963 lm	36-E*1-F2-2036-***-***
2106	LED	1x47W / 5134 lm	36-E*1-F2-2106-***-***
2176	LED	1x49W / 5305 lm	36-E*1-F2-2176-***-***
2246	LED	1x50W / 5476 lm	36-E*1-F2-2246-***-***
2316	LED	1x52W / 5647 lm	36-E*1-F2-2316-***-***
2386	LED	1x53W / 5818 lm	36-E*1-F2-2386-***-***
2456	LED	1x55W / 5989 lm	36-E*1-F2-2456-***-***
2526	LED	1x56W / 6160 lm	36-E*1-F2-2526-***-***
2596	LED	1x58W / 6332 lm	36-E*1-F2-2596-***-***
2666	LED	1x60W / 6503 lm	36-E*1-F2-2666-***-***
2736	LED	1x61W / 6674 lm	36-E*1-F2-2736-***-***
2806	LED	1x63W / 6845 lm	36-E*1-F2-2806-***-***

Custom lengths also available, please contact us

*Luminous flux taken at 4000K Opal diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC	36-EF1-F-***-***-D
		OPAL	36-EH1-F-***-***-C
		BLACK OPAL	36-EN1-F-***-***-B
BLACK OPAL			

OUTPUT

Low Output	Medium Output	High Output	Low Output	36-E*1-F1-***-***-A
			Medium Output	36-E*1-F2-***-***-A
			High Output	36-E*1-F3-***-***-A

Low Output approximately 29% decrease in power & 27% decrease in lumens against Medium Output
High Output approximately 39% increase in power & 33% increase in lumens against Medium Output

CRI

80	90	97	80	36-E*1-F-***-g***-A
			90	36-E*1-F-***-g***-A
			97	36-E*1-F-***-g***-A

COLOUR TEMPERATURE

2700K	3000K	4000K	5000K	2700 K	36-E*1-F-***-27***-A
				3000 K	36-E*1-F-***-30***-A
				4000 K	36-E*1-F-***-40***-A
				5000 K	36-E*1-F-***-50***-A

CONTROL

NON DIM	DALI DIM	DALI 2 DIM	CASAMBI	NON DIM	36-E*1-F-***-K***-A
				DALI DIM	36-E*1-F-***-J***-A
				DALI 2 DIM	36-E*1-F-***-JA***-A
				CASAMBI DIM	36-E*1-F-***-BL***-A

*Easy/Air Io T on request

EMERGENCY

NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY	3 HOUR REPORTING EMERGENCY	3 HOUR SELF-TEST EMERGENCY	No Emergency	36-E*1-F-***-0***-A
				3 Hour Non Reporting EM	36-E*1-F-***-3***-A
				3 Hour Reporting EM	36-E*1-F-***-4***-A
				3 Hour Self-Test EM	36-E*1-F-***-5***-A

*Only available in sizes above 1266mm.

FINISH

BLACK	WHITE	GREY	CUSTOM RAL	BLACK	36-E*1-F-***-***-D
				WHITE	36-E*1-F-***-***-C
				GREY	36-E*1-F-***-***-B
				CUSTOM RAL	36-E*1-F-***-***-RAL###

