



LOPEN SURFACE

Versatile by Nature.

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM

The LOPEN Surface is a clean-cut continuous linear profile with outstanding performance and efficiency. Designed with simplicity and attention to detail in mind, this profile luminaire is the intelligent solution for compact yet powerful and energy-efficient lighting. The modular and continuous LED lighting system Lopen enhances a contemporary feel of any architectural space, creating clean lines of light with its LED light source.

The Lopen enables the design hungry environments to have true freedom with its variation of mounting styles, combinations of connections and illuminated corners. The diverse range of lengths can be combined to create intriguing design or simply blend in with the architecture

PRODUCT CODE

LOPEN SURFACE DIRECT		
L (mm)	Medium Output	
706	LED 1x16W / 1727 lm	11-F*1-F2-706-***-***-***
776	LED 1x18W / 1900 lm	11-F*1-F2-776-***-***-***
846	LED 1x19W / 2072 lm	11-F*1-F2-846-***-***-***
916	LED 1x21W / 2245 lm	11-F*1-F2-916-***-***-***
986	LED 1x22W / 2418 lm	11-F*1-F2-986-***-***-***
1056	LED 1x24W / 2590 lm	11-F*1-F2-1056-***-***-***
1126	LED 1x25W / 2763 lm	11-F*1-F2-1126-***-***-***
1196	LED 1x27W / 2936 lm	11-F*1-F2-1196-***-***-***
1266	LED 1x28W / 3108 lm	11-F*1-F2-1266-***-***-***
1336	LED 1x30W / 3281 lm	11-F*1-F2-1336-***-***-***
1406	LED 1x32W / 3454 lm	11-F*1-F2-1406-***-***-***
1476	LED 1x33W / 3627 lm	11-F*1-F2-1476-***-***-***
1546	LED 1x35W / 3799 lm	11-F*1-F2-1546-***-***-***
1616	LED 1x36W / 3972 lm	11-F*1-F2-1616-***-***-***
1686	LED 1x38W / 4144 lm	11-F*1-F2-1686-***-***-***
1756	LED 1x39W / 4317 lm	11-F*1-F2-1756-***-***-***
1826	LED 1x41W / 4490 lm	11-F*1-F2-1826-***-***-***
1896	LED 1x42W / 4662 lm	11-F*1-F2-1896-***-***-***
1966	LED 1x44W / 4835 lm	11-F*1-F2-1966-***-***-***
2036	LED 1x46W / 5008 lm	11-F*1-F2-2036-***-***-***
2106	LED 1x47W / 5180 lm	11-F*1-F2-2106-***-***-***
2176	LED 1x49W / 5353 lm	11-F*1-F2-2176-***-***-***
2246	LED 1x50W / 5526 lm	11-F*1-F2-2246-***-***-***
2316	LED 1x52W / 5699 lm	11-F*1-F2-2316-***-***-***
2386	LED 1x53W / 5871 lm	11-F*1-F2-2386-***-***-***
2456	LED 1x55W / 6044 lm	11-F*1-F2-2456-***-***-***
2526	LED 1x56W / 6216 lm	11-F*1-F2-2526-***-***-***
2596	LED 1x58W / 6389 lm	11-F*1-F2-2596-***-***-***
2666	LED 1x60W / 6562 lm	11-F*1-F2-2666-***-***-***
2736	LED 1x61W / 6734 lm	11-F*1-F2-2736-***-***-***
2806	LED 1x63W / 6907 lm	11-F*1-F2-2806-***-***-***

Custom lengths also available, please contact us

*Luminous flux taken at 4000K, Opal diffuser

OUTPUT

Low Output	Medium Output	High Output	Low Output Medium Output High Output <small>*Low output approximately 29% decrease in power & 28% decrease in lumens against Medium Output High output approximately 36% increase in power & 33% increase in lumens against Medium Output</small>	11-F*1-F1-***-***-***-*** 11-F*1-F2-***-***-***-*** 11-F*1-F3-***-***-***-***
------------	---------------	-------------	--	---

CRI

80	90	97	11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** <small>*CRI97 not available with office optics</small>
----	----	----	--

COLOUR TEMPERATURE

2700K	3000K	4000K	5000K	TW 2700K-5000K	11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** <small>*Tunable White only available on High Output fittings with a length over 1266</small>
-------	-------	-------	-------	-------------------	--

CONTROL

NON DIM	DALI DIM	DALI2 DIM	CASAMBI	NON DIM DALI DIM DALI 2 DIM CASAMBI DIM <small>*EasyAir IoT on request</small>	11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-***
---------	----------	-----------	---------	--	--

EMERGENCY

NO EMERGENCY	3 HOUR NON-REPORTING EMERGENCY	3 HOUR REPORTING EMERGENCY	3 HOUR SELF-TEST EMERGENCY	No Emergency 3 Hour Non Reporting EM 3 Hour Reporting EM 3 Hour Self-Test EM <small>*Only available in sizes above 1266mm.</small>	11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-***
--------------	--------------------------------	----------------------------	----------------------------	--	--

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC OPAL ASYMMETRIC BLACK OPAL DROP PRISMATIC DROP OPAL	11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-*** 11-F*1-F-***-***-***-***
ASYMMETRIC	BLACK OPAL		
DROP PRISMATIC	DROP OPAL		

FINISH

BLACK	WHITE	GREY	CUSTOM RAL	BLACK WHITE GREY CUSTOM RAL 11-F*1-F-***-***-***-***-RAL####
-------	-------	------	------------	--

