



LOPEN WALL

Versatile by Nature

PRODUCT DESCRIPTION

MOUNTING	WALL
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE

The LOPEN Wall is a clean-cut continuous linear profile with outstanding performance and efficiency. Designed with simplicity and attention to detail in mind, this profile luminaire is the intelligent solution for compact yet powerful and energy-efficient lighting. The wall mounted linear slot system Lopen enhances a contemporary feel of any architectural space, creating clean lines of light with its LED light source.

The Lopen enables the design hungry environments to have true freedom with its variation of mounting styles, combinations of connections and illuminated corners. The diverse range of lengths can be combined to create intriguing design or simply blend in with the architecture.

PRODUCT CODE

LOPEN WALL		
L (mm)	High Efficiency	
561mm	LED 12.4W / 1630 lm	11-J*1-F2-561-8***-0-*
847mm	LED 24W / 3150 lm	11-J*1-F2-847-8***-0-*
1127mm	LED 24.8W / 3270 lm	11-J*1-F2-1127-8***-0-*
1408mm	LED 31W / 4090 lm	11-J*1-F2-1408-8***-0-*
1688mm	LED 37.2W / 4910 lm	11-J*1-F2-1688-8***-0-*
1969mm	LED 43.4W / 5720 lm	11-J*1-F2-1969-8***-0-*
2249mm	LED 49.6W / 6540 lm	11-J*1-F2-2249-8***-0-*
2810mm	LED 62W / 8180 lm	11-J*1-F2-2810-8***-0-*
3371mm	LED 74.4W / 9820 lm	11-J*1-F2-3371-8***-0-*
4493mm	LED 99.2W / 13090 lm	11-J*1-F2-4493-8***-0-*
	High Output	
561mm	LED 21.9W / 2670 lm	11-J*1-F3-561-8***-0-*
847mm	LED 33.6W / 4160 lm	11-J*1-F3-847-8***-0-*
1127mm	LED 43.8W / 5350 lm	11-J*1-F3-1127-8***-0-*
1408mm	LED 54.8W / 6690 lm	11-J*1-F3-1408-8***-0-*
1688mm	LED 65.7W / 8030 lm	11-J*1-F3-1688-8***-0-*
1969mm	LED 76.7W / 9370 lm	11-J*1-F3-1969-8***-0-*
2249mm	LED 87.6W / 10710 lm	11-J*1-F3-2249-8***-0-*
2810mm	LED 109.5W / 13390 lm	11-J*1-F3-2810-8***-0-*
3371mm	LED 131.4W / 16060 lm	11-J*1-F3-3371-8***-0-*
4493mm	LED 175.2W / 21420 lm	11-J*1-F3-4493-8***-0-*

* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS		
OPAL	MICROPRISMATIC	OPAL PRISMATIC 11-J*1-F*-***-8***-0-*
COLOUR TEMPERATURE		
3000K	4000K	3000K 11-J*1-F*-***-830-0-*
4000K 11-J*1-F*-***-840-0-*		
CONTROL		
NON DIM	DALIDIM	DALI DIM BLUETOOTH
NON DIM	DALI DIM	B.DALI DIM
NON DIM 11-J*1-F*-***-8***-K-*		
DALI DIM 11-J*1-F*-***-8***-J-*		
B.DALI DIM 11-J*1-F*-***-8***-M-*		
EMERGENCY		
NO EMERGENCY	3 HOUR EMERGENCY	0 HR 11-J*1-F*-***-8***-0-*
		3 HR 11-J*1-F*-***-8***-3-*
* Emergency available in 1122mm+		
FINISH		
WHITE	BLACK	SILVER
WHITE	BLACK	SILVER
		WHITE 11-J*1-F*-***-8***-C
		BLACK 11-J*1-F*-***-8***-D
		SILVER 11-J*1-F*-***-8***-B