

NILE SUSPENDED

Suspended Tubular Omnidirectional Lighting

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - DIRECT/INDIRECT
MATERIALS	PC / ALUMINIUM
OPTIC	OPAL DIFFUSER

Minimalist and classic in design, the Nile is a clean cut tubular luminaire that can add a personality to your design. The clean aesthetics and satin diffuser will enhance any modern space allowing the light to add an extra layer of presence in the environment. Suspend it horizontally or vertically, at an obscure angle, or jazz it up with a red coloured suspension cable, the choice is yours.

Powered by LED COB technology, the tubular diffuser distributes soft and uniform light in an omni-directional style for a comfortable level of illumination whilst keeping the energy consumption in check.


Ideal as a creative feature luminaire for breakout spaces, reception areas and public areas.

PRODUCT CODE

NILE SUSPENDED DIRECT

L (mm)	High Efficiency	
Ø75 x 852mm	LED 15W / 1875 lm	55-EH1-F1-852-***-0-*
Ø75 x 1132mm	LED 19W / 2375 lm	55-EH1-F1-1132-***-0-*
Ø75 x 1692mm	LED 28W / 4000 lm	55-EH1-F1-1692-***-0-*
Ø75 x 1972mm	LED 30W / 4295 lm	55-EH1-F1-1972-***-0-*
Ø75 x 2252mm	LED 35W / 5330 lm	55-EH1-F1-2252-***-0-*
	High Output	
Ø75 x 852mm	LED 32W / 4650 lm	55-EH1-F3-852-***-0-*
Ø75 x 1132mm	LED 41W / 4350 lm	55-EH1-F3-1132-***-0-*
Ø75 x 1692mm	LED 52W / 6350 lm	55-EH1-F3-1692-***-0-*
Ø75 x 1972mm	LED 60W / 8344 lm	55-EH1-F3-1972-***-0-*
Ø75 x 2252mm	LED 69W / 10215 lm	55-EH1-F3-2252-***-0-*

* Luminous Flux taken with 4000K / Opal Diffuser



CRI

80	90	80	55-EH*-F*-***-8**-*-0-*
		90	55-EH*-F*-***-9**-*-0-*

COLOUR TEMPERATURE

3000K	4000K	3000K	55-EH*-F*-***-30-*-0-*
		4000K	55-EH*-F*-***-40-*-0-*

CONTROL

NONDIM	DALIDIM	NON DIM	55-EH*-F*-***-***-K-0-*
		DALI DIM	55-EH*-F*-***-***-J-0-*

*CASAMBI (integrated controls)

FINISH

WHITE	BLACK	WHITE	55-EH*-F*-***-***-*-0-C
		BLACK	55-EH*-F*-***-***-*-0-D

NILE SUSPENDED DIRECT/INDIRECT

L (mm)	LED 22W / 1915 lm	55-EH3-F1-852-***-0-*
Ø70 x 885mm	LED 31W / 2750 lm	55-EH3-F1-1132-***-0-*
Ø70 x 1245mm	LED 38W / 3420 lm	55-EH3-F1-1692-***-0-*
Ø70 x 1530mm	LED 45W / 4089 lm	55-EH3-F1-1972-***-0-*
Ø70 x 1815mm	LED 51W / 4594 lm	55-EH3-F1-2252-***-0-*
Ø70 x 2030mm		

* Luminous Flux taken with 4000K / Opal Diffuser

