



Oxbow

Totally unique.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED/SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	360°
MATERIALS	SILICONE

Minimalist and totally unique in design just like the bend in the river, the Oxbow is a novelty architectural lighting. The LED rope light brings an element of excitement, adding personality to your design.

The clean aesthetics of the neon tube will enhance any modern space allowing the light to add an extra layer. Suspend it horizontally or vertically, at an obscure angle, the choice is yours.

Powered by LED technology, the Oxbow distributes soft light in an omni-directional style. With up to 20 m reel in length that could be cut exactly to measure, and a diverse range of accessories to allow multiple mounting methods, the led rope light is ideal as a creative feature luminaire for breakout spaces, reception areas and retail.

PRODUCT CODE

OXBOW		
	OXBOW Ø25mm	
l (mm)		
1000mm	LED 1x 24V / 950lm/M	86-SI3-F1*-****-9***-0-C
1000mm	LED 1x 48V / 1000lm/M	86-SI3-F2*-****-9***-0-C
1000mm	LED 1x 24V / 1140lm/M	86-SI3-F3*-****-9***-0-C
*24V up to 5m, 48V up to 20m *Luminous Flux take at 4000K		
ACCESSORIES		
1M Linear Pendant Mounting		86-1
Vertical Suspension Kit		86-2
Vertical Suspension Kit with 2.5m Tube		86-3
Horizontal Suspension Kit		86-4
Horizontal Suspension Kit with tube		86-5
Adjustable Solid Rod Mounting Kit		86-6
Surface Mounting Kit		86-7
Concealed Surface Mounting Kit		86-8
End Cap Surface Mounting Kit		86-9
Horizontal Suspension Connection		86-10
Connection Kit		86-11
Plaster In Recessed Kit		86-12
Recessed Kit		86-13
Decorative Node Plate		86-14
Decorative Single Node		86-15
Decorative Double Node		86-16

MOUNTING		SURFACE		SUSPENDED	
SURFACE	SUSPENDED	86-FSI3-F**-*--9***-0-C	86-ESI3-F**-*--9***-0-C		
CABLE ENTRY		END CAP	SIDE ENTRY	86-SI3-F**-*--9***-0-C	86-SI3-F**-*--9***-0-C
COLOUR TEMPERATURE		2300K	2700K	3000K	4000K
2300K	2700K	3000K	4000K	86-SI3-F**-*--923***-0-C	86-SI3-F**-*--927***-0-C
				86-SI3-F**-*--930***-0-C	86-SI3-F**-*--940***-0-C
CONTROL		NON DIM	DALI DIM	CASAMBI	
NON DIM	DALI DIM	CASAMBI		86-SI3-F**-*--9***-J-C-0-C	86-SI3-F**-*--9***-J-C-0-C
				86-SI3-F**-*--9***-BL-0-C	

