

RIO RECESSED TRIMLESS

The Game Changer.

PRODUCT DESCRIPTION

MOUNTING	RECESSED TRIMLESS
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	COMPLETE

The RIO Recessed Trimless is the ultimate performance driven slim linear profile. Designed with simplicity and attention to detail, the RIO is contemporary and stylish. With its variation in mounting styles and diffusers, the RIO is a perfect example of flexible linear LED lighting. A true all-rounder, it is equally at home in an office and as linear architectural lighting. The RIO can be also specified as asymmetric wall washer for applications where illuminating a vertical wall is required, such as accent lighting or retail lighting.


Used as an individual luminaire in standard size, or a continuous linear lighting system, the RIO adds a contemporary feel to any workplace or architectural space. Specified with the opal diffuser, the RIO Recessed creates clean smooth lines of light, in crisp plasterboard.

PRODUCT CODE

RIO RECESSED TRIMLESS

L (mm)	High Efficiency	High Output
860mm	LED 1x19W / 2399 lm	58-B*1-F23-***-0-*
1140mm	LED 1x28W / 3598 lm	58-B*1-F35-***-0-*
1420mm	LED 1x35W / 4398 lm	58-B*1-F43-***-0-*
1700mm	LED 1x41W / 5198 lm	58-B*1-F51-***-0-*
2260mm	LED 1x50W / 6397 lm	58-B*1-F63-***-0-*
860mm	LED 1x27W / 3191 lm	58-B*1-F31-***-0-*
1140mm	LED 1x40W / 4786 lm	58-B*1-F47-***-0-*
1420mm	LED 1x48W / 5849 lm	58-B*1-F58-***-0-*
1700mm	LED 1x57W / 6913 lm	58-B*1-F69-***-0-*
2260mm	LED 1x70W / 8508 lm	58-B*1-F85-***-0-*

* Luminous Flux taken with 4000K / Microprismatic Diffuser



OPTICS

MICROPRISMATIC	OPAL	ASYMMETRIC	PRISMATIC OPAL ASYMMETRIC BLACK OPAL MOD NARROW MOD WIDE	58-BF1-F**-*-*-* 58-BH1-F**-*-*-* 58-BB1-F**-*-*-* 58-BN1-F**-*-*-* 58-BZ31-F**-*-*-* 58-BZ61-F**-*-*-*
BLACK OPAL	MODULAR NARROW BEAM	MODULAR WIDE BEAM		

CRI

80	90	80	58-B*1-F**-*3**-*
		90	58-B*1-F**-*4**-*

COLOUR TEMPERATURE

3000K	4000K	TW 2700K-5000K	3000K 4000K TW	58-B*1-F**-*30**-* 58-B*1-F**-*40**-* 58-B*1-F**-*TW-J**-*
-------	-------	-------------------	----------------------	---

CONTROL

NONDIM	DALI DIM	NON DIM DALI DIM	58-B*1-F**-*K**-* 58-B*1-F**-*J**-*
--------	----------	---------------------	--

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR 3 HR	58-B*1-F**-*0**-* 58-B*1-F**-*3**-*
--------------	---------------------	--------------	--

*Only available in sizes above 1700mm.

FINISH

BLACK	WHITE	GREY	BLACK WHITE GREY	58-B*1-F**-*D**-* 58-B*1-F**-*C**-* 58-B*1-F**-*B**-*
-------	-------	------	------------------------	--

INTERNAL REFLECTOR (MODULAR OPTIC ONLY)

BLACK	WHITE	BLACK WHITE	58-B*1-F**-*D**-* 58-B*1-F**-*C**-*
-------	-------	----------------	--

RIO RECESSED TRIMLESS

The Game Changer.

PRODUCT DESCRIPTION

MOUNTING	RECESSED TRIMLESS
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
LUMINAIRE TYPE	SYSTEM

The RIO Recessed Trimless is the ultimate performance driven slim linear profile. Designed with simplicity and attention to detail, the RIO is contemporary and stylish. With its variation in mounting styles and diffusers, the RIO is a perfect example of flexible linear LED lighting. A true all-rounder, it is equally at home in an office and as linear architectural lighting. The RIO can be also specified as asymmetric wall washer for applications where illuminating a vertical wall is required, such as accent lighting or retail lighting.

Used as an individual luminaire in standard size, or a continuous linear lighting system, the RIO adds a contemporary feel to any workplace or architectural space. Specified with the opal diffuser, the RIO Recessed creates clean smooth lines of light, in crisp plasterboard.

PRODUCT CODE

RIO RECESSED TRIMLESS START MODULES

High Efficiency	LED	Beam	LM	Product Code
580	LED	1x13W	1407	58-B*1-F2-50x580-***-***-*
650	LED	1x14W	1582	58-B*1-F2-50x650-***-***-*
720	LED	1x16W	1758	58-B*1-F2-50x720-***-***-*
790	LED	1x18W	1934	58-B*1-F2-50x790-***-***-*
860	LED	1x19W	2110	58-B*1-F2-50x860-***-***-*
930	LED	1x21W	2286	58-B*1-F2-50x930-***-***-*
1000	LED	1x22W	2461	58-B*1-F2-50x1000-***-***-*
1070	LED	1x24W	2637	58-B*1-F2-50x1070-***-***-*
1140	LED	1x25W	2813	58-B*1-F2-50x1170-***-***-*
1210	LED	1x27W	2989	58-B*1-F2-50x1210-***-***-*
1280	LED	1x28W	3164	58-B*1-F2-50x1280-***-***-*
1350	LED	1x33W	3692	58-B*1-F2-50x1350-***-***-*
1490	LED	1x35W	3868	58-B*1-F2-50x1490-***-***-*
1560	LED	1x36W	4043	58-B*1-F2-50x1560-***-***-*
1630	LED	1x38W	4219	58-B*1-F2-50x1630-***-***-*
1700	LED	1x39W	4395	58-B*1-F2-50x1700-***-***-*
1840	LED	1x41W	4571	58-B*1-F2-50x1840-***-***-*
1910	LED	1x42W	4746	58-B*1-F2-50x1910-***-***-*
1980	LED	1x44W	4922	58-B*1-F2-50x1980-***-***-*
2050	LED	1x46W	5098	58-B*1-F2-50x2050-***-***-*
2120	LED	1x47W	5274	58-B*1-F2-50x2120-***-***-*
2190	LED	1x49W	5450	58-B*1-F2-50x2190-***-***-*
2260	LED	1x50W	5625	58-B*1-F2-50x2260-***-***-*
2330	LED	1x52W	5801	58-B*1-F2-50x2330-***-***-*
2400	LED	1x53W	5977	58-B*1-F2-50x2400-***-***-*
2470	LED	1x55W	6153	58-B*1-F2-50x2470-***-***-*
2540	LED	1x56W	6328	58-B*1-F2-50x2540-***-***-*
2610	LED	1x58W	6504	58-B*1-F2-50x2610-***-***-*
2680	LED	1x60W	6680	58-B*1-F2-50x2680-***-***-*
2750	LED	1x61W	6856	58-B*1-F2-50x2750-***-***-*
2820	LED	1x63W	7032	58-B*1-F2-50x2820-***-***-*



*Luminous flux taken at 4000K Opal diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC	58-BF1-F-***x***-***-***-*
		OPAL	58-BH1-F-***x***-***-***-*
		ASYMMETRIC	58-BB1-F-***x***-***-***-*
		BLACK OPAL	58-BN1-F-***x***-***-***-*
		MOD NARROW	58-BZ31-F-***x***-***-***-*
		MOD WIDE	58-BZ61-F-***x***-***-***-*
ASYMMETRIC	BLACK OPAL		
MODULAR NARROW BEAM	MODULAR WIDE BEAM		

CRI

80	90	80	58-B*1-F*-50x***-g**-*-*
		90	58-B*1-F*-50x***-g**-*-*

COLOUR TEMPERATURE

2700K	3000K	2700 K	58-B*1-F*-50x***-27-*-*
		3000 K	58-B*1-F*-50x***-30-*-*
		4000 K	58-B*1-F*-50x***-40-*-*
		5000 K	58-B*1-F*-50x***-50-*-*
		TW	58-B*1-F*-50x***-TW-*-*
4000K	5000K		
TW	2700K-5000K		

CONTROL

NONDIM	DALIDIM	NON DIM	58-B*1-F*-50x***-***-J(-)*
		DALI DIM	58-B*1-F*-50x***-***-J(+)*

*Casambi and EasyAir controls on request

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	58-B*1-F*-50x***-***-0-*
		3 HR	58-B*1-F*-50x***-***-3-*

*Only available in sizes above 1266mm.

FINISH

BLACK	WHITE	BLACK	58-B*1-F*-50x***-***-*.D
		WHITE	58-B*1-F*-50x***-***-*.C
		GREY	58-B*1-F*-50x***-***-*.B
GREY			

INTERNAL REFLECTOR (MODULAR OPTIC ONLY)

BLACK	WHITE	BLACK	58-B*1-F*-50x***-***-*.D
		WHITE	58-B*1-F*-50x***-***-*.C