

RYDAL SURFACE

Halo Circular Luminaire.

PRODUCT DESCRIPTION

MOUNTING	SURFACE
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT
MATERIALS	ALUMINIUM
OPTIC	MICROPRIMATIC / OPAL
WIDTH	60MM

The RYDAL adds an instant visual presence to any commercial lighting requirement. Thanks to its flexible nature, the RYDAL is an ideal architectural luminaire for bespoke designs. The RYDAL can be tailored to your design with a diameter of up to 8m.

The 60 mm wide and 65mm deep body is ideal for breakout spaces or reception areas where a strong visual presence is required.


The smaller sizes are a great choice for office lighting and circulation areas. The light is uniform, efficient and comfortable.

PRODUCT CODE

RYDAL SURFACE DIRECT

L (mm)	High Efficiency	
Ø900 x 60mm	LED 72.5W / 6253 lm	46-F*1-F1-900-***-0-*
Ø1200 x 60mm	LED 97W / 8379 lm	46-F*1-F1-1200-***-0-*
Ø1500 x 60mm	LED 116W / 10005 lm	46-F*1-F1-1500-***-0-*
Ø1800 x 60mm	LED 145W / 12506 lm	46-F*1-F1-1800-***-0-*
Ø2400 x 60mm	LED 188.5W / 16258 lm	46-F*1-F1-2400-***-0-*
Ø3000 x 60mm	LED 239W / 20635 lm	46-F*1-F1-3000-***-0-*
High Output		
Ø900 x 60mm	LED 131W / 10219 lm	46-F*1-F3-900-***-0-*
Ø1200 x 60mm	LED 175W / 13693 lm	46-F*1-F3-1200-***-0-*
Ø1500 x 60mm	LED 209W / 16350 lm	46-F*1-F3-1500-***-0-*
Ø1800 x 60mm	LED 261W / 20438 lm	46-F*1-F3-1800-***-0-*
Ø2400 x 60mm	LED 339W / 26569 lm	46-F*1-F3-2400-***-0-*
Ø3000 x 60mm	LED 431W / 33722 lm	46-F*1-F3-3000-***-0-*

* Luminous Flux taken with 4000K / Opal Diffuser



OPTICS

MICROPRISMATIC	OPAL	PRISMATIC 46-F**F*-***-***-0-*
		OPAL 46-F**F*-***-***-0-*

CRI

80	90	80 46-F**F*-***-8**-0-*
		90 46-F**F*-***-9**-0-*

COLOUR TEMPERATURE

3000K	4000K	3000K 46-F**F*-***-30-0-*
		4000K 46-F**F*-***-40-0-*

CONTROL

NON DIM	DALI DIM	NON DIM 46-F**F*-***-K-0-*
		DALI DIM 46-F**F*-***-J-0-*
		CASAMBI 46-F**F*-***-C-0-*
		PHASE DIM 46-F**F*-***-M-0-*

*CASAMBI (integrated controls)

FINISH

WHITE	BLACK	WHITE 46-F**F*-***-0-C
		BLACK 46-F**F*-***-0-D
		SILVER 46-F**F*-***-0-B
SILVER		

