



# TAMEGA SUSPENDED

The Power Of Geometry.

## PRODUCT DESCRIPTION

<b>MOUNTING</b>	SUSPENDED
<b>LIGHT SOURCE</b>	LED
<b>LIGHT DISTRIBUTION</b>	DIRECT, DIRECT / INDIRECT
<b>MATERIALS</b>	ALUMINIUM

\*Product is also available as surface, wall and recessed mounting styles.  
More details are coming soon. Please contact the office for further information.

## PRODUCT CODE

TAMEGA SUSPENDED DIRECT	
Leg length (mm)	High Efficiency
846 mm	<b>LED</b> 152W / 16880 lm <b>73-F*1-F2-846-***-***-***</b>
1266mm	<b>LED</b> 224W / 25312 lm <b>73-F*1-F2-1266-***-***-***</b>
1546mm	<b>LED</b> 280W / 30944 lm <b>73-F*1-F2-1546-***-***-***</b>
1826mm	<b>LED</b> 328W / 36568 lm <b>73-F*1-F2-1826-***-***-***</b>
2246mm	<b>LED</b> 400W / 45000 lm <b>73-F*1-F2-2246-***-***-***</b>
	High Output
846 mm	<b>LED</b> 216W / 22448 lm <b>73-F*1-F3-846-***-***-***</b>
1266mm	<b>LED</b> 320W / 33672 lm <b>73-F*1-F3-1266-***-***-***</b>
1546mm	<b>LED</b> 384W / 41152 lm <b>73-F*1-F3-1546-***-***-***</b>
1826mm	<b>LED</b> 456W / 48632 lm <b>73-F*1-F3-1826-***-***-***</b>
2246mm	<b>LED</b> 560W / 59856 lm <b>73-F*1-F3-2246-***-***-***</b>

\* Luminous Flux taken with 4000K / Opal Diffuser

TAMEGA SUSPENDED DIRECT / INDIRECT	
Leg length (mm)	High Efficiency
846 mm	<b>LED</b> 280W / 33408 lm <b>73-F*3-F2-846-***-***-***</b>
1266mm	<b>LED</b> 424W / 51624 lm <b>73-F*3-F2-1266-***-***-***</b>
1546mm	<b>LED</b> 528W / 63768 lm <b>73-F*3-F2-1546-***-***-***</b>
1826mm	<b>LED</b> 624W / 75912 lm <b>73-F*3-F2-1826-***-***-***</b>
2246mm	<b>LED</b> 776W / 94136 lm <b>73-F*3-F2-2246-***-***-***</b>
	High Output
846 mm	<b>LED</b> 384W / 44424 lm <b>73-F*3-F3-846-***-***-***</b>
1266mm	<b>LED</b> 600W / 68656 lm <b>73-F*3-F3-1266-***-***-***</b>
1546mm	<b>LED</b> 736W / 84808 lm <b>73-F*3-F3-1546-***-***-***</b>
1826mm	<b>LED</b> 872W / 100968 lm <b>73-F*3-F3-1826-***-***-***</b>
2246mm	<b>LED</b> 1089W / 125200 lm <b>73-F*3-F3-2246-***-***-***</b>

\* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS		
MICROPRISMATIC	OPAL	PRISMATIC <b>73-F*F*F****-***-***-***</b>
		OPAL <b>73-F*H*F****-***-***-***</b>

\* Nero optic available on request

CRI		
80	90	80 <b>73-F**F****-8**-***-***</b>
		90 <b>73-F**F****-9**-***-***</b>
COLOUR TEMPERATURE		
2700K	3000K	2700K <b>73-F**F****-27-***-***</b>
		3000K <b>73-F**F****-30-***-***</b>
		4000K <b>73-F**F****-40-***-***</b>
		5000K <b>73-F**F****-50-***-***</b>
		TW <b>73-F**F****-TW-***-***</b>
4000K	5000K	
TW	2700-5000K	

CONTROL		
NON DIM	DALIDIM	NON DIM <b>73-F**F****-K-***-***</b>
		DALI DIM <b>73-F**F****-J-***-***</b>
		EASY AIR PIR <b>73-F**F****-Q-***-***</b>
		DALI DIM B. <b>73-F**F****-M-***-***</b>
EasyAir PIR/ Daylight DIM	DALI DIM BLUETOOTH	

EMERGENCY		
NO EMERGENCY	3 HOUR EMERGENCY	0 HR <b>73-F**F****-0-***-***</b>
		3 HR <b>73-F**F****-3-***-***</b>

FINISH		
WHITE	BLACK	WHITE <b>73-F**F****-***-***-C</b>
		BLACK <b>73-F**F****-***-***-D</b>
		SILVER <b>73-F**F****-***-***-B</b>
SILVER		



SCAN  
TAMEGA  
PRODUCT