

# TINTO SUSPENDED

The Power Of Geometry.

## PRODUCT DESCRIPTION

<b>MOUNTING</b>	SUSPENDED
<b>LIGHT SOURCE</b>	LED
<b>LIGHT DISTRIBUTION</b>	DIRECT, DIRECT / INDIRECT
<b>MATERIALS</b>	ALUMINIUM

Product is also available as Surface, Wall and Recessed mounting styles.


More details are coming soon. Please contact the office for further information.

## PRODUCT CODE

### TINTO SUSPENDED DIRECT

Leg length (mm)	High Efficiency	
846 mm	LED 38W / 4220 lm	70-F*1-F2-846-***-***
1266mm	LED 56W / 6328 lm	70-F*1-F2-1266-***-***
1546mm	LED 70W / 7736 lm	70-F*1-F2-1546-***-***
1826mm	LED 82W / 9142 lm	70-F*1-F2-1826-***-***
2246mm	LED 100W / 11250 lm	70-F*1-F2-2246-***-***
2526mm	LED 112W / 12656 lm	70-F*1-F2-2526-***-***
High Output		
846 mm	LED 54W / 5612 lm	70-F*1-F3-846-***-***
1266mm	LED 80W / 8418 lm	70-F*1-F3-1266-***-***
1546mm	LED 96W / 10288 lm	70-F*1-F3-1546-***-***
1826mm	LED 114W / 12158 lm	70-F*1-F3-1826-***-***
2246mm	LED 140W / 14964 lm	70-F*1-F3-2246-***-***
2526mm	LED 158W / 16834 lm	70-F*1-F3-2526-***-***


\* Luminous Flux taken with 4000K / Opal Diffuser



### TINTO SUSPENDED DIRECT / INDIRECT

Leg length (mm)	High Efficiency	
846 mm	LED 70W / 8352 lm	70-F*3-F2-846-***-***
1266mm	LED 106W / 12906 lm	70-F*3-F2-1266-***-***
1546mm	LED 132W / 15942 lm	70-F*3-F2-1546-***-***
1826mm	LED 156W / 18978 lm	70-F*3-F2-1826-***-***
2246mm	LED 194W / 23534 lm	70-F*3-F2-2246-***-***
2526mm	LED 218W / 26570 lm	70-F*3-F2-2526-***-***
High Output		
846 mm	LED 96W / 11106 lm	70-F*3-F3-846-***-***
1266mm	LED 150W / 17164 lm	70-F*3-F3-1266-***-***
1546mm	LED 184W / 21202 lm	70-F*3-F3-1546-***-***
1826mm	LED 218W / 25242 lm	70-F*3-F3-1826-***-***
2246mm	LED 272W / 31300 lm	70-F*3-F3-2246-***-***
2526mm	LED 306W / 35338 lm	70-F*3-F3-2526-***-***

\* Luminous Flux taken with 4000K / Opal Diffuser



### OPTICS

MICROPRISMATIC	OPAL	PRISMATIC	70-F**F*-***-***-***
		OPAL	70-F**F*-***-***-***

\* Nero optic available on request

### CRI

80	90	80	70-F**F*-***-8**-***
		90	70-F**F*-***-9**-***

### COLOUR TEMPERATURE

2700K	3000K	2700K	70-F**F*-***-27-***
		3000K	70-F**F*-***-30-***
		4000K	70-F**F*-***-40-***
		5000K	70-F**F*-***-50-***
		TW	70-F**F*-***-TW-***
TW		2700-5000K	

### CONTROL

NONDIM	DALIDIM	NON DIM	70-F**F*-***-K-***
		DALI DIM	70-F**F*-***-J-***
		EASY AIR PIR	70-F**F*-***-Q-***
		DALI DIM B.	70-F**F*-***-M-***
EasyAir PIR/ Daylight DIM	DALI DIM BLUETOOTH		

### EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	70-F**F*-***-0-***
		3 HR	70-F**F*-***-3-***

### FINISH

WHITE	BLACK	WHITE	70-F**F*-***-***-C
		BLACK	70-F**F*-***-***-D
		SILVER	70-F**F*-***-***-B
SILVER			



SCAN  
TINTO  
PRODUCT