



TURIA SUSPENDED

The Power Of Geometry.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT, DIRECT / INDIRECT
MATERIALS	ALUMINIUM

The TURIA Suspended is a performance driven linear profile based on an equilateral triangle. It is simple, contemporary and sleek. Used as an individual pendant luminaire or a cluster of triangles, Turia adds a playful feel to any workplace or architectural spaces, guaranteed to stand out. And the best thing about Turia? The luminaire is supplied pre assembled as one unit, meaning a super easy installation!


*Product is also available as surface, recessed trim and trimless mounting styles.

PRODUCT CODE

TURIA SUSPENDED DIRECT

Leg length (mm)	High Efficiency	
846 mm	LED 57W / 6330 lm	67-F*1-F2-846-***-***-***
1266mm	LED 84W / 9492 lm	67-F*1-F2-1266-***-***-***
1546mm	LED 105W / 11604 lm	67-F*1-F2-1546-***-***-***
1826mm	LED 123W / 13713 lm	67-F*1-F2-1826-***-***-***
2246mm	LED 150W / 16875 lm	67-F*1-F2-2246-***-***-***
2526mm	LED 168W / 18984 lm	67-F*1-F2-2526-***-***-***
High Output		
846 mm	LED 81W / 8418 lm	67-F*1-F3-846-***-***-***
1266mm	LED 120W / 12627 lm	67-F*1-F3-1266-***-***-***
1546mm	LED 144W / 15432 lm	67-F*1-F3-1546-***-***-***
1826mm	LED 171W / 18237 lm	67-F*1-F3-1826-***-***-***
2246mm	LED 210W / 22446 lm	67-F*1-F3-2246-***-***-***
2526mm	LED 237W / 25251 lm	67-F*1-F3-2526-***-***-***

* Luminous Flux taken with 4000K / Opal Diffuser



TURIA SUSPENDED DIRECT / INDIRECT

Leg length (mm)	High Efficiency	
846 mm	LED 105W / 12528 lm	67-F*3-F2-846-***-***-***
1266mm	LED 159W / 19359 lm	67-F*3-F2-1266-***-***-***
1546mm	LED 198W / 23913 lm	67-F*3-F2-1546-***-***-***
1826mm	LED 234W / 28467 lm	67-F*3-F2-1826-***-***-***
2246mm	LED 291W / 35301 lm	67-F*3-F2-2246-***-***-***
2526mm	LED 327W / 39855 lm	67-F*3-F2-2526-***-***-***
High Output		
846 mm	LED 144W / 16659 lm	67-F*3-F3-846-***-***-***
1266mm	LED 225W / 25746 lm	67-F*3-F3-1266-***-***-***
1546mm	LED 276W / 31803 lm	67-F*3-F3-1546-***-***-***
1826mm	LED 327W / 37863 lm	67-F*3-F3-1826-***-***-***
2246mm	LED 408W / 46950 lm	67-F*3-F3-2246-***-***-***
2526mm	LED 459W / 53007 lm	67-F*3-F3-2526-***-***-***

* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS

MICROPRISMATIC	OPAL	PRISMATIC	67-F*F*-F*-***-***-***
		OPAL	67-FH*-F*-***-***-***

* Nero optic available on request



CRI

80	90	80	67-F**-F*-***-***-***
		90	67-F**-F*-***-***-***

COLOUR TEMPERATURE

2700K	3000K	2700K	67-F**-F*-***-***-***
		3000K	67-F**-F*-***-***-***
		4000K	67-F**-F*-***-***-***
		5000K	67-F**-F*-***-***-***
		TW	67-F**-F*-***-***-***
		TW	2700-5000K

CONTROL

NON DIM	DALI DIM	NON DIM	67-F**-F*-***-***-***
		DALI DIM	67-F**-F*-***-***-***
		EASY AIR PIR	67-F**-F*-***-***-***
		DALI DIM B.	67-F**-F*-***-***-***
Easy Air PIR / Daylight DIM	DALI DIM BLUETOOTH		

EMERGENCY

NO EMERGENCY	3 HOUR EMERGENCY	0 HR	67-F**-F*-***-***-***
		3 HR	67-F**-F*-***-***-***

FINISH

WHITE	BLACK	WHITE	67-F**-F*-***-***-***-C
		BLACK	67-F**-F*-***-***-***-D
		SILVER	67-F**-F*-***-***-***-B
SILVER			