



RYDAL SUSPENDED

Halo Circular Pendant.

PRODUCT DESCRIPTION

MOUNTING	SUSPENDED
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	DIRECT - DIRECT / INDIRECT
MATERIALS	ALUMINIUM
OPTIC	MICROPRISMATIC / OPAL
WIDTH	60MM

The RYDAL adds an instant visual presence to any commercial lighting requirement. Thanks to its flexible nature, the RYDAL is an ideal architectural luminaire for bespoke designs. The RYDAL can be tailored to your design with a diameter of up to 8m.

The 60 mm wide and 65mm deep body is ideal for large spaces or atrium's where a strong visual presence is required. Emitting direct and indirect light, these LED luminaires distribute homogeneous soft light.

The smaller sizes are a great choice for office lighting, breakout spaces and circulation areas. The light is uniform, efficient and comfortable.

PRODUCT CODE

RYDAL SUSPENDED DIRECT

L (mm)	Medium Output	
Ø603 x 65mm	LED 23W / 2220 lm	46-E*1-F2-603-***-***-*
Ø800 x 65mm	LED 31W / 2960 lm	46-E*1-F2-800-***-***-*
Ø1140 x 65mm	LED 46W / 4450 lm	46-E*1-F2-1140-***-***-*
Ø1515 x 65mm	LED 61W / 5840 lm	46-E*1-F2-1515-***-***-*
Ø2050 x 65mm	LED 84W / 8150 lm	46-E*1-F2-2050-***-***-*
Ø2440 x 65mm	LED 99W / 9640 lm	46-E*1-F2-2440-***-***-*
Ø2980 x 65mm	LED 122W / 11860 lm	46-E*1-F2-2980-***-***-*
High Output		
Ø603 x 65mm	LED 32W / 3040 lm	46-E*1-F3-603-***-***-*
Ø800 x 65mm	LED 42W / 4060 lm	46-E*1-F3-800-***-***-*
Ø1140 x 65mm	LED 64W / 6090 lm	46-E*1-F3-1140-***-***-*
Ø1515 x 65mm	LED 85W / 8000 lm	46-E*1-F3-1515-***-***-*
Ø2050 x 65mm	LED 117W / 11170 lm	46-E*1-F3-2050-***-***-*
Ø2440 x 65mm	LED 138W / 13200 lm	46-E*1-F3-2440-***-***-*
Ø2980 x 65mm	LED 170W / 16250 lm	46-E*1-F3-2980-***-***-*

* Luminous Flux taken with 4000K / Opal Diffuser

RYDAL SUSPENDED DIRECT / INDIRECT

L (mm)	Medium Output	
Ø603 x 65mm	LED 29W / 2880 lm	46-E*3-F2-603-***-***-*
Ø800 x 65mm	LED 38W / 3840 lm	46-E*3-F2-800-***-***-*
Ø1140 x 65mm	LED 61W / 6200 lm	46-E*3-F2-1140-***-***-*
Ø1515 x 65mm	LED 76W / 7680 lm	46-E*3-F2-1515-***-***-*
Ø2050 x 65mm	LED 107W / 10790 lm	46-E*3-F2-2050-***-***-*
Ø2440 x 65mm	LED 130W / 13150 lm	46-E*3-F2-2440-***-***-*
Ø2980 x 65mm	LED 153W / 15370 lm	46-E*3-F2-2980-***-***-*
High Output		
Ø603 x 65mm	LED 40W / 3900 lm	46-E*3-F3-603-***-***-*
Ø800 x 65mm	LED 53W / 5260 lm	46-E*3-F3-800-***-***-*
Ø1140 x 65mm	LED 85W / 8500 lm	46-E*3-F3-1140-***-***-*
Ø1515 x 65mm	LED 106W / 10530 lm	46-E*3-F3-1515-***-***-*
Ø2050 x 65mm	LED 148W / 14780 lm	46-E*3-F3-2050-***-***-*
Ø2440 x 65mm	LED 180W / 18010 lm	46-E*3-F3-2440-***-***-*
Ø2980 x 65mm	LED 212W / 21060 lm	46-E*3-F3-2980-***-***-*

* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS

MICROPRISMATIC	OPAL	MICROPRISMATIC & OPAL	PRISMATIC 46-E**F-***-8***-***-*
			OPAL 46-E**F-***-8***-***-*
			PRISMATIC & OPAL 46-E**F-***-8***-***-*

* Prismatic & Opal only on Indirect/Direct fittings.

COLOUR TEMPERATURE

3000K	4000K	TW 2700-6500K	3000K 46-E**F-***-830-***-*
			4000K 46-E**F-***-840-***-*
			TW 46-E**F-***-8TW-J-***-*

*TW not available with DALI Dimming

CONTROL

NON DIM	DALI DIM	NON DIM 46-E**F-***-8**K-***-*
		DALI DIM 46-E**F-***-8**J-***-*

*PIR Sensor & other controls available on request

EMERGENCY

NON EMERGENCY	3HR NON-REPORTING EMERGENCY	3HR REPORTING EMERGENCY	3HR SELF-TEST EMERGENCY	NON-EMERGENCY 46-E**F-***-8**0-***-*
				3 HR NON-REPORTING 46-E**F-***-8**3-***-*
				3 HR REPORTING 46-E**F-***-8**4-***-*
				3 HR SELF-TEST 46-E**F-***-8**5-***-*

FINISH

BLACK	WHITE	SILVER	BLACK 46-E**F-***-8**A-D-***-*
			WHITE 46-E**F-***-8**A-C-***-*
			SILVER 46-E**F-***-8**A-B-***-*

