

# TALLA SURFACE

The Timeless.

## PRODUCT DESCRIPTION

<b>MOUNTING</b>	SURFACE
<b>LIGHT SOURCE</b>	LED
<b>LIGHT DISTRIBUTION</b>	DIRECT - DIRECT/INDIRECT
<b>MATERIALS</b>	ALUMINIUM
<b>OPTICS</b>	MICROPRISMATIC / OPAL

The architectural office lighting Talla uses the idea of basic geometrical shapes and timeless appearance to produce a luminaire which delivers simplicity at its best. Variation in sizes, multiple colour choices and the selection of dimming options means the Talla can now add a personality to any space.

The option of an opal diffuser gives a clean and contemporary look, with the evenly distributed light enhancing the details of a building's architecture.

## PRODUCT CODE

### TALLA SURFACE DIRECT

L (mm)		
400x62mm	LED 19W /2270lm	21-F*1-F1-400-8**-*-*
400x62mm	LED 30W /3580lm	21-F*1-F2-400-8**-*-*
500x62mm	LED 30W /3810lm	21-F*1-F1-500-8**-*-*
500x62mm	LED 46W /5650lm	21-F*1-F2-500-8**-*-*
600x62mm	LED 31W /4240lm	21-F*1-F1-600-8**-*-*
600x62mm	LED 45W /5900lm	21-F*1-F2-600-8**-*-*
600x62mm	LED 55W /7110lm	21-F*1-F3-600-8**-*-*
850x62mm	LED 59W /8070lm	21-F*1-F1-850-8**-*-*
850x62mm	LED 81W /10920lm	21-F*1-F2-850-8**-*-*
850x62mm	LED 98W /13080lm	21-F*1-F3-850-8**-*-*

\*Luminous Flux taken with 4000K / Opal Diffuser

### TALLA SURFACE DIRECT / INDIRECT

L (mm)		
400x62mm	LED 16W /2090lm	21-F*3-F1-400-8**-*-*
400x62mm	LED 28W /3490lm	21-F*3-F2-400-8**-*-*
500x62mm	LED 30W /3870lm	21-F*3-F1-500-8**-*-*
500x62mm	LED 45W /5760lm	21-F*3-F2-500-8**-*-*
600x62mm	LED 24W /3290lm	21-F*3-F1-600-8**-*-*
600x62mm	LED 40W /5390lm	21-F*3-F2-600-8**-*-*
600x62mm	LED 55W /7160lm	21-F*3-F3-600-8**-*-*
850x62mm	LED 49W /6700lm	21-F*3-F1-850-8**-*-*
850x62mm	LED 81W /10940lm	21-F*3-F2-850-8**-*-*
850x62mm	LED 89W /11920lm	21-F*3-F3-850-8**-*-*

\*Luminous Flux taken with 4000K / Opal Diffuser

### OPTICS

MICROPRISMATIC	OPAL	MICROPRISMATIC & OPAL	PRISMATIC 21-F**F*-***-8**-*-*
			OPAL 21-FH**F*-***-8**-*-*
			PRISMATIC 21-FFH**F*-***-8**-*-* & OPAL

\*Prismatic & Opal only on indirect/Direct fittings

### COLOUR TEMPERATURE

3000K	4000K	TW 2700-6500K	3000K 21-F**F*-***-830-*-*
			4000K 21-F**F*-***-840-*-*
			TW 21-F**F*-***-8TW-J-*-*

\*TW not available with DALI Dimming

### CONTROL

NON DIM	DALIDIM	NON DIM 21-F**F*-***-8**-*-*
		DALI DIM 21-F**F*-***-8**-*-*

\*PIR Sensor & other controls available on request


### EMERGENCY

NON EMERGENCY	3HR NON-REPORTING EMERGENCY	3HR REPORTING EMERGENCY	3HR SELF-TEST EMERGENCY	NON-EMERGENCY 21-F**F*-***-8**-*-*
				3 HR NON-REPORTING 21-F**F*-***-8**-*-*
				3 HR REPORTING 21-F**F*-***-8**-*-*
				3 HR SELF-TEST 21-F**F*-***-8**-*-*

### FINISH

BLACK	WHITE	SILVER	BLACK 21-F**F*-***-8**-*-*
			WHITE 21-F**F*-***-8**-*-*
			SILVER 21-F**F*-***-8**-*-*

Direct Light Distribution



Direct/Indirect Light Distribution

