



TALLA SUSPENDED

The Timeless.

PRODUCT DESCRIPTION

| | |
|---------------------------|--------------------------|
| MOUNTING | SUSPENDED |
| LIGHT SOURCE | LED |
| LIGHT DISTRIBUTION | DIRECT - DIRECT/INDIRECT |
| MATERIALS | ALUMINIUM |
| OPTIC | MICROPRISMATIC / OPAL |

The architectural office lighting Talla uses the idea of basic geometrical shapes and timeless appearance to produce a luminaire which delivers simplicity at its best. Variation in sizes, multiple colour choices and the selection of dimming options means the Talla can now add a personality to any space.

The option of an opal diffuser gives a clean and contemporary look, with the evenly distributed light enhancing the details of a building's architecture.

TALLA SUSPENDED DIRECT

| L (mm) | | |
|----------|--------------|------------------------|
| 400x62mm | 19W /2270lm | 21-E*1-F1-400-8***-*** |
| 400x62mm | 30W /3580lm | 21-E*1-F2-400-8***-*** |
| 500x62mm | 30W /3810lm | 21-E*1-F1-500-8***-*** |
| 500x62mm | 46W /5650lm | 21-E*1-F2-500-8***-*** |
| 600x62mm | 31W /4240lm | 21-E*1-F1-600-8***-*** |
| 600x62mm | 45W /5900lm | 21-E*1-F2-600-8***-*** |
| 600x62mm | 55W /7110lm | 21-E*1-F3-600-8***-*** |
| 850x62mm | 59W /8070lm | 21-E*1-F1-850-8***-*** |
| 850x62mm | 81W /10920lm | 21-E*1-F2-850-8***-*** |
| 850x62mm | 98W /13080lm | 21-E*1-F3-850-8***-*** |

* Luminous Flux taken with 4000K / Opal Diffuser

TALLA SUSPENDED DIRECT / INDIRECT

| L (mm) | | |
|----------|--------------|------------------------|
| 400x62mm | 16W /2090lm | 21-E*3-F1-400-8***-*** |
| 400x62mm | 28W /3490lm | 21-E*3-F2-400-8***-*** |
| 500x62mm | 30W /3870lm | 21-E*3-F1-500-8***-*** |
| 500x62mm | 45W /5760lm | 21-E*3-F2-500-8***-*** |
| 600x62mm | 24W /3290lm | 21-E*3-F1-600-8***-*** |
| 600x62mm | 40W /5390lm | 21-E*3-F2-600-8***-*** |
| 600x62mm | 55W /7160lm | 21-E*3-F3-600-8***-*** |
| 850x62mm | 49W /6700lm | 21-E*3-F1-850-8***-*** |
| 850x62mm | 81W /10940lm | 21-E*3-F2-850-8***-*** |
| 850x62mm | 89W /11920lm | 21-E*3-F3-850-8***-*** |

* Luminous Flux taken with 4000K / Opal Diffuser

OPTICS

| | | | |
|----------------|------|-----------------------|------------------------------------|
| MICROPRISMATIC | OPAL | MICROPRISMATIC & OPAL | PRISMATIC 21-E*F*-F*-***-8***-*** |
| | | | OPAL 21-E*H*-F*-***-8***-*** |
| | | | PRISMATIC 21-E*FH*-F*-***-8***-*** |
| | | | & OPAL |

*Prismatic & Opal only on Indirect/Direct fittings

COLOUR TEMPERATURE

| | | |
|-------|-------|----------------------------|
| 3000K | 4000K | 3000K 21-E*-F*-***-830-*** |
| | | 4000K 21-E*-F*-***-840-*** |

CONTROL

| | | |
|---------|----------|---------------------------------|
| NON DIM | DALI DIM | NON DIM 21-E*-F*-***-8**-(C)-** |
| | | DALI DIM 21-E*-F*-***-8**-J-*** |

*PIR Sensor & other controls available on request

EMERGENCY

| | | | | |
|---------------|-----------------------------|-------------------------|-------------------------|-------------------------------------------|
| NON EMERGENCY | 3HR NON-REPORTING EMERGENCY | 3HR REPORTING EMERGENCY | 3HR SELF-TEST EMERGENCY | NON-EMERGENCY 21-E**-F***-8***-0-*** |
| | | | | 3 HR NON-REPORTING 21-E**-F***-8***-3-*** |
| | | | | 3 HR REPORTING 21-E**-F***-8***-4-*** |
| | | | | 3 HR SELF-TEST 21-E**-F***-8***-5-*** |

FINISH

| | | | |
|-------|-------|--------|---------------------------|
| BLACK | WHITE | SILVER | BLACK 21-E**-F***-8***-D |
| | | | WHITE 21-E**-F***-8***-C |
| | | | SILVER 21-E**-F***-8***-B |

