



PRODUCT DESCRIPTION

MOUNTING
LIGHT SOURCE
LIGHT DISTRIBUTION
MATERIALS
OPTIC

PRODUCT CODE

616mm LED 19W / 2370 lm

896mm LED 29W / 3560 lm

1176mm LED 38.5W / 4740 lm

1456mm LED 48W / 5930 lm 1736mm LED 58W / 7120 lm

2016mm LED 67.5W / 8300 lm

2296mm LED 77W / 9490 lm

* Luminous Flux taken with 4000K / Opal Diffu

ERIE SURFACE

SURFACE LED INDIRECT ALUMINIUM OPAL

49-FH2-F1-616-8**-*-0-*

49-FH2-F1-896-8**-*-0-*

49-FH2-F1-1176-8**-*-0-*

49-FH2-F1-1456-8**-*-0-*

49-FH2-F1-1736-8**-*-0-*

49-FH2-F1-2016-8**-*-0-*

49-FH2-F1-2296-8**-*-0-*

Unique in design, the Erie adds a contemporary feel to any office space. Made with attention to detail, this high-quality luminaire offers an effective way of lighting spaces with low ceilings.

An all-round solution with a choice of 7 lengths and a broad range of joints and accessories, the Erie is a pioneering lighting system that allows for a comprehensive range of applications using just linear indirect light. Its innovative profile design is just 37mm deep, with chamfered edges to emphasise a thin, seamless luminaire.

Used as a single unit or a sophisticated system, it is guaranteed to be noticed.

COLOUR TEMPE	RATURE		
3000K	4000K	3000K 4000K	49-FH2-F*-***-830-*-0-* 49-FH2-F*-***-840-*-0-*
CONTROL			
NON DIM	DALIDIM	NON DIM DALI DIM	
FINISH			
WHITE	BLACK	WHITE BLACK SILVER	49-FH2-F*-***-8**-*-0-C 49-FH2-F*-***-8**-*-0-D 49-FH2-F*-***-8**-*-0-B
SILVER			

